



Technical Details

Metric

Inch

Operating conditions		
Maximum speed	0.55 m/sec	1.5 ft/sec
Temperature range	-30°C + 90°C	-22°F + 194°F
Maximum pressure	17 Bar	250 p.s.i

Maximum extrusion gap

Pressure bar	17
Maximum gap mm	250
Pressure p.s.i	0.030

Surface roughness

	µmRa	µmRt	µinCLA	µinRMS
Dynamic sealing surface ØD ₁ in	0.8 max	5 max	32 max	35 max
Static sealing face Ød ₁	1.6 max	10 max	63 max	70 max
Static Housing faces L ₁	3.2 max	16 max	125 max	140 max

Chamfers & Radii

Seal diameter ≤ ØD ₁ in	2.000	3.000	6.500
Min chamfer C in	0.187	0.217	0.250
Max fillet rad r ₁ in	0.062	0.093	0.125

DESIGN

The PKCUPC is designed for the use of single or double acting light duty applications.

It is responsive to low pressure fluctuations and has low friction. Additionally, it is ideal for the use in pneumatic applications and also suitable for use in mineral oil based fluids and water.

FEATURES

- Flexible for easy installation
- Long life
- Comes in a wide range of sizes

MATERIAL

Seal design comes in a variety of materials and sizes. For more information, please refer to MSDS datasheet.

APPLICATIONS

Light duty applications