# OZ 6000X



### Complete seal manufacturing system includes:

- Granulator
- Seal manufacturing software and hardware (over 250 profiles)
- Swarf extraction system with cyclon seperator
- Complete set of Toolbox (inclues holders, cutting tools and spares)
- Freight, training and installation on site



## OZ 6000X

#### **Features**

- Machining seals up to a diameter of 660mm
- Manufacture seals at high speeds of up to 1500rpm
- Uses the Servo motor on its spindle
- Fully equipped with swarf extraction system and toolbox
- CAD/CAM software developed exclusively by Oz Seals
- Oz Seals aluminium adjustable clamping system

### Standard configuration

- X/Z axes linear guideway, tailstock hard rectangle guideway
- GSK CNC controller (OPT: SIEMENS, FANUC)
- X/Z axes driver&motor: GSK brand AC servo
- Spindle: ECO top brand Servo Motor&Driver
- Hydraulic chuck (TAIWAN brand thru-hole chuck 10" & thru-hole rotary oil)
- TAIWAN brand 10 station Hydraulic tool turret (OPT: 12 station)
- Automatical lubrication, Tri-color indication lamp, coolant system, working lamp, heat exchanger, pedal switch
- Front door lock by sensor, side door lock by bolts (According to CE safety standard)









#### Machine package inclusions:



Computer/CAD CAM Software



Industrial vacuum



Clamping system

## **OZ 6000X**













## Specification :

Item	Specification	Unit	
Capacity	Max. swing dia. over bed	mm	Ф660
	Max. swing dia. over slide	mm	Ф500
	Recommended turning dia.	mm	Ф380
	Max. turning dia	mm	Ф600
	Max. turning length	mm	350
Spindle	Spindle bore	mm	Ф86
	Spindle type	1	A2-8
	Spindle speed	rpm	1500
	Chuck size	1	10" (OPT: 12" chuck)
	Max. bar through dia.	mm	Ф 74
	Spindle motor power	Kw	18.5
X/Z axes	X axes travel	mm	400
	Z axes travel	mm	860/1640/2150/3150
	X/Z axes rapid moving speed	m/min	16(Linear guideway); 12(Box guideway)
Tool turret	Tool turret type	1	Hydraulic 12 station
	Toolshank size	mm	25x25, Φ40
Tailstock	Tailstock quill taper	1	MT5# rotary
	Tailstock quill dia./travel	mm	Ф150/150
	Tailstock guideway	1	Rectangle guideway
Others	Machining roughness	mm	Ra≤1.6
	Machining accuracy	1	IT6
	X/Z axes repeated positioning accuracy	mm	0.008/0.01 (0.013)
	Overall size	mm	4400x2200x2000
	N.W.	kg	3600

## Main parts list:

Item	Brand	
CNC controller	OPT: SIEMENS/FANUC/GSK	
Feeding driver & motor	OPT: SIEMENS/FANUC/GSK	
Spindle driver & motor	OPT: SIEMENS/FANUC/GSK	
Spindle unit	TAIWAN-LOSEN/KENTURN	
Spindle encoder	GERMANY-HEIDENHAIN	
Servo powered tool turret	GERMANY-SAUTER	
Ball screw	TAIWAN-PMI/HIWIN	
Ball screw bearing	JAPAN-NSK/TAIWAN-TPI	
Linear guideway	TAIWAN PMI/HIWIN	
Lubrication system	TAIWAN-ISHAN	
Rotary oil cylinder & chuck	TAIWAN-CH-H	
Hydraulic parts	TAIWAN/JAPAN	
Coolant pumps	Joint-venture	
MPG	USA-HEDSS	

ltem	Brand	
Tri-colour indication lamp	KOREA-QLIGHT	
Isolation transformer	CHINA-top-CHINT/JIUKO	
Breaker	FRANCE-SCHNEIDER	
AC contactor	FRANCE-SCHNEIDER	
Relay	JAPAN-OMRON	
Dc switching mode power supply	TAIWAN-MEANWELL	
Terminal block	GERMANY-WEIDMULLER	
Synchronous belt	USA-GATES	
Synchronous belt wheel	TAIWAN - PTP	
Nuts	TAIWAN-YINSH	
Shaft coupling	GERMANY-KTR/R+W	
Extensible cover	TAIWAN-WANHE	
Chip conveyor & chip bucket	TAIWAN-WANHE	
Coolant pipe	TAIWAN-WEIDING	

### Seal manufacturing software & hardware

Item	
Vacuum/ Swarf collection system	Swarf granulator (SPAENE FRESSER)
	Adjustable suction line swarf collection chamber 44 gallon and coolant recycling system
Computer	Brand new computer with latest Windows operating system
Software	Latest Windows operating software
	Simploz turning software
	Oz Seals manufacturing software
	Post processor

## Toolbox (Holders, cutting tools & spares):

ltem	Tools/ Holders
1 Toolholder & Tool (OZ 1 - 2)	DO -
1 Toolholder & Tool (OZ 3 - 4)	)—(E
1 Toolholder & Tool (OZ 3 – 4 R)	
1 Toolholder & Tool (OZ 5-6)	
1 Toolholder & Tool (OZ 7 - 19)	
1 Toolholder & Tool (OZ 8)	<i>p</i> -
1 Toolholder & Tool (OZ 9)	
1 Toolholder & Tool (OZ 10)	
1 Toolholder & Tool (OZ 11 - 12)	
1 Toolholder & Tool (OZ 13 - 14)	-
1 Toolholder & Tool (OZ 15 - 18)	
1 Toolholder & Tool (OZ 22)	
1 Toolholder & Tool (OZ 22 V)	-
1 Toolholder & Tool (OZ 23 - 24)	<b>₫</b> ─
1 Toolholder & Tool (OZ 25)	4

Item	Tools/ Holders
1 Toolholder & Tool (OZ 26 - 27)	
1 Toolholder & Tool (OZ 28)	<b>→</b>
1 Toolholder & Tool (OZ 31)	
1 Toolholder & Tool (OZ 32S)	- 0
12 Holder Holders (to take holders) OZ UNI OPT TURRET: 8 or 12	
1 Spike holder (to make chevron seals)	<b>—= (1-11</b>
1 Right hand boring bar 20mm	
1 Left hand boring bar 16mm	